

INDUSTRIAL COMPONENT DATA

SPT 5/ 4-V-7,5-ZB WH/BU/RD/BK 1704653 PHOENIX CONTACT

Terminal block for printed circuit board, rated curren..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPT 5/ 4-V-7,5-ZB WH/BU/RD/BK

PRODUCT IMAGE\nNOT
AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	SPT 5/ 4-V-7,5-ZB WH/BU/RD/BK
Catalog number	1704653
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-4F39D50654
Generated	2026-09-23

Product Overview

Terminal block for printed circuit board, rated current: 41 A, rated voltage: 1000 V, pitch: 7.5 mm, number of poles: 4, connection type: Push-in spring connection, mounting: Wave soldering, driver/printed circuit board connection direction: 90 °, color: multicolor

Terminal for printed circuit board, nominal current: 41 A, nominal voltage (III/2): 1000 V, nominal section: 6 mm², number of rows: 1, number of poles per row: 4, family of articles: SPT 5/.. -V, pitch: 7.5 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 90 °, color: multicolor, Pin arrangement: Zigzag Pins W, Pin length [P]: 4.6 mm, number of solder pins per potential: 1, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

PCB terminal block, nominal current: 41 A, nom. voltage: 1000 V, pitch: 7.5 mm, number of positions: 4, connection method: Push-in spring connection, mounting: Wave soldering, conductor/PCB connection direction: 90 °, color: multi-color

Your advantages

Time saving push-in connection, tools not requiredDefined contact force ensures that contact remains stable over the long termClamping space opened by means of fixed screwdriver enables convenient conductor connectionUnrestricted

600-V-UL approval thanks to compact zig-zag pinningVertical connection enables multi-row arrangement on the PCBKey Commercial Data

Orderkey 1704653

Packing unit 1

GTIN 4046356731362
Custom tariff number 85369010
Material data - housing
Housing color multi-color
Dimensions for the product
Length [l] 18.5 mm
Width [w] 31.8 mm
Height (without solder pin) 24.15 mm
Solder pin [P] 4.6 mm
Dimension a 22.5 mm
Pin spacing 14 mm
Dimensions for PCB design
Hole diameter 2.1 mm
Pin spacing 14 mm
Packaging information
Type of packaging packed in cardboard
Pieces per package 50
Denomination packing units Pcs.
Air clearances and creepage distances
Voltage 800 V
Standards and Regulations
Connection in acc. with standard EN-VDE
CUL
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
eCl@ss
eCl@ss 4.0 272607xx
eCl@ss 4.1 27260701
eCl@ss 5.0 27260701
eCl@ss 5.1 27141190
eCl@ss 6.0 27260704
eCl@ss 7.0 27440402
eCl@ss 8.0 274...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPT 5/ 4-V-7,5-ZB WH/BU/RD/BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.