


INDUSTRIAL COMPONENT DATA

SPTA 1,5/ 7-5,08 MC 1511631 PHOENIX CONTACT Terminal block for printed circuit board, nominal current: 17.5 ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPTA 1,5/ 7-5,08 MC



Manufacturer	PHOENIX CONTACT
MPN / Reference	SPTA 1,5/ 7-5,08 MC
Catalog number	1511631
Category	Printed circuit board terminal
Minimum order	2000 Pcs
Document ID	EO-D4F18D48C7
Generated	2026-09-29

Product Overview

Terminal block for printed circuit board, nominal current: 17.5 A, nominal voltage (III/2): 320 V, nominal cross-section: 1.5 mm², number of rows: 1, number of poles per row: 7, article family: SPTA 1.5/, pitch: 5.08 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 45 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.4 mm, number of welding pins per potential: 2, packaging type: boxed

PCB terminal, rated current: 9 A, rated voltage (III/2): 320 V, rated cross-section: 1.5 mm², number of rows: 1, number of poles per row: 7, item family: SPTA 1.5/, pitch: 5.08 mm, connection type: Push-in spring connection, mounting: Wave soldering, connection direction conductor/printed circuit board: 45°, Color: Green, Pin Arrangement: Linear Pin Arrangement, Pin Length [P]: 3.4mm, Number of Solder Pins by Potential: 2, Packing Type: Boxed Packaging

PCB terminal block, nominal current: 17.5 A, rated voltage (III/2): 320 V, nominal cross section: 1.5 mm², number of rows: 1, number of positions per row: 7, product range: SPTA 1,5/, pitch: 5.08 mm, connection method: Push-in spring connection, mounting: Wave soldering, conductor/PCB connection direction: 45 °, color: green, Pin layout: Linear pinning, Solder pin [P]: 3.4 mm, number of solder pins per potential: 2, type of packaging: packed in....

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Technical dataProduct propertiesProduct line COMBICON Terminals S

Product type Printed circuit board terminal

Product family SPTA 1,5/

Number of positions 7
Pitch 5.08 mm
Number of rows 1
Pin layout Linear pinning
Solder pins per potential 2
Electrical propertiesNominal current I_N 17.5 A
Nominal voltage U_N 320 V
Degree of pollution 3
Rated voltage (III/3) 250 V
Rated surge voltage (III/3) 4 kV
Rated voltage (III/2) 320 V
Rated surge voltage (III/2) 4 kV
Rated voltage (II/2) 630 V
Rated surge voltage (II/2) 4 kV
Connection dataConnection technology
Nominal cross section 1.5 mm²
Conductor connection
Connection method Push-in spring connection
Conductor cross section rigid 0.2 mm² ... 1.5 mm²
Conductor cross section flexible 0.2 mm² ... 1.5 mm²
Conductor cross section AWG 24 ... 16
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 1.5 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 1.5 mm²
Stripping length 10 mm
MountingMounting type Wave soldering
Pin layout Linear pinning
Material specificationsMaterial data - contact
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201
Contact material Cu alloy
Surface characteristics hot-dip tin-plated
Metal surface terminal point (top layer) Tin (4 - 8 µm Sn)
Metal surface soldering area (top layer) Tin (4 - 8 µm Sn)
Material data - housing
Color (Housing) green (6021)
Insulating material PA
Insulating material group I
CTI according to I...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPTA 1,5/ 7-5,08 MC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.