

INDUSTRIAL COMPONENT DATA

SPTA-THR 1,5/ 2-5,08 R32 1071199 PHOENIX CONTACT

Terminal for printed circuit board, rated current: 13,5 A, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SPTA-THR 1,5/ 2-5,08 R32

PRODUCT IMAGE\nNOT
AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	SPTA-THR 1,5/ 2-5,08 R32
Catalog number	1071199
Category	Printed circuit board terminal
Minimum order	145 Pcs
Document ID	EO-00B9317C90
Generated	2026-09-28

Product Overview

Terminal for printed circuit board, rated current: 13,5 A, pitch: 5,08 mm, number of poles: 2, Connection type: spring clamp push-in, mounting: Weld THR, direction for Connection conductor/pcb: 45 °, color: black

Terminal block for printed circuit board, nominal current: 13.5 A, nominal voltage (III/2): 320 V, nominal section: 1.5 mm², number of rows: 1, number of poles per row: 2, family of articles: SPTA 1.5/.. -THR, pitch: 5.08 mm, connection type: Push-in spring connection, mounting: Weld THR, conductor connection direction/printed circuit board: 45°, color: black, Pin arrangement: Linear pin arrangement, Pin length [P]: 2.6 mm, number of solder pins per potential: 1, packaging type: 32 mm wide strap

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SPTA-THR 1,5/ 2-5,08 R32 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.