INDUSTRIAL COMPONENT DATA

ST-17S1N8AWQ00S 1607654 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST-17S1N8AWQ00S



Manufacturer	PHOENIX CONTACT
MPN / Reference	ST-17S1N8AWQ00S
Catalog number	1607654
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-207CBB37DB
Generated	2026-11-18

Product Overview

Device connector, front mounting
Conect. plug. to be apar. front wall, straight, for standard and SPEEDCON locking, M17, number of poles: 17, contact type: Female, Axial O-ring, 4x Ø2.7, shielded: yes, flange size: 21.6 mm x 21.6 mm, protection index: IP67, number of poles: 17, connection type: Crimped connection, series: ST

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1607654
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 63 (C-2-2017)
GTIN 4046356273626
Weight per Piece (excluding packing) 27.000 g
Custom tariff number 85366990
Country of origin DE (Germany)
General
Note Order information: Order crimp contacts Ø 0.6 mm separately
Type of locking for standard and SPEEDCON interlock

Direction of rotation of contact chamber numbering Standard
Coding N
Contact connection method Crimp connection
Type of contacts Socket
Number of positions 17
Contact diameter of power contacts 0.6 mm
Nominal current per power contact at 25°C 3.6 A
Pg housing screw connection none
Mounting type 4x Ø2,7
Ambient conditions
Ambient temperature -40 °C ... 125 °C
Degree of protection IP67
Material
Housing material Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Insulator material PA 6.6
Gasket and O-ring material FPM
Specifications according to DIN EN 61984:2001
Installation height max. 3000 m
Nominal / operating voltage of power contacts 60 V
Rated surge voltage of power contacts 1.5 kV
Overvoltage category of power contacts III
Degree of pollution of power contacts 3
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027143424eCl@ss 5.127143400eCl@ss 6.027279200eCl@ss 7.027440103eCl@ss 8.027440103eC...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST-17S1N8AWQ00S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.