INDUSTRIAL COMPONENT DATA

# ST 2,5-QUATTRO-DIO 1N 5408K/L-R 3002216 PHOENIX CONTACT Component terminal block

**Brand: PHOENIX CONTACT | Manufacturer Part Number: ST 2,5-QUATTRO-DIO 1N 5408K/L-R**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | ST 2,5-QUATTRO-DIO 1N 5408K/L-R |
| Catalog number | 3002216 |
| Category | Component terminal block |
| Minimum order | 50 Pcs |
| Document ID | EO-DA98CF7FF9 |
| Generated | 2026-11-19 |

## Product Overview

Component terminal block
Terminal block for components, with 1N 5408K diode installed, nominal voltage: 800 V, nominal current: 1.5 A, connection type: Spring connection, Dimensioning section: 1 mm², cross-section: 0.08 mm² - 4 mm², mounting: NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Modular TBs |

## Additional Product Information

Key Commercial Data
Orderkey 3002216
Packing unit 50 pc
Minimum order quantity 50 pc
Catalog page Page 164 (C-1-2017)
GTIN 4055626210421
Weight per Piece (excluding packing) 9.530 g
Custom tariff number 85369010
Country of origin PL (Poland)
General
Number of levels 1
Number of connections 4

Potentials 1
Nominal cross section 2.5 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Maximum load current the maximum current is determined by the diode
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.77 W
Maximum load current 1.5 A (the maximum current is determined by the diode)
Nominal current IN 1.5 A
Nominal voltage UN 800 V
Open side panel Yes
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 9.8 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 2 kV
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed
Result of bending test Test passed
Bending test rotation speed 10 rpm
Bending test turns 135
Bending test conductor cross section/weight 0.08 mm² / 0.1 kg
2.5 mm² / 0.7 kg
4 mm² / 0.9 kg
Tensile test result Test passed
Conductor cross section tensile test 0.08 mm²
Tractive force setpoint 5....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST 2,5-QUATTRO-DIO 1N 5408K/L-R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.