INDUSTRIAL COMPONENT DATA

ST-3EP1N8AW400S 1607674 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST-3EP1N8AW400S



Manufacturer	PHOENIX CONTACT
MPN / Reference	ST-3EP1N8AW400S
Catalog number	1607674
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-6382DC2E85
Generated	2026-11-18

Product Overview

Device connector, front mounting
Conect. plug. to be apar. front wall, straight, for standard and SPEEDCON locking, M17, number of poles: 3+PE, contact type: Male, shielded: yes, flange measurement: 21.6 mm x 21.6 mm, protection index: IP67, number of poles: 4, connection type: Crimped connection, series: ST

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1607674
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 139 (C-2-2017)
GTIN 4046356273817
Weight per Piece (excluding packing) 27.700 g
Custom tariff number 85366990
Country of origin DE (Germany)
General
Note Order information: Order crimp contacts Ø 2 mm separately
Type of locking for standard and SPEEDCON interlock

Direction of rotation of contact chamber numbering Standard
Coding N
Contact connection method Crimp connection
Type of contacts Pin
Number of positions 4
Contact diameter of power contacts 2 mm
Nominal current per power contact at 25°C 25 A
Contact diameter of signal contacts 2 mm
Pg housing screw connection none
Ambient conditions
Ambient temperature -40 °C ... 125 °C
Degree of protection IP67
Specifications according to DIN EN 61984:2001
Installation height max. 3000 m
Nominal / operating voltage of power contacts 630 V
Rated surge voltage of power contacts 6 kV
Overvoltage category of power contacts III
Degree of pollution of power contacts 3
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027143424eCl@ss 5.127143400eCl@ss 6.027279200eCl@ss 7.027440103eCl@ss 8.027440103eCl@ss 9.027440102
ETIM 3.0EC001121ETIM 4.0EC001121ETIM 5.0EC002061ETIM 6.0EC002061
UNSPSC 6.0143172015UNSPSC 7.090143201404UNSPSC 1143172015UNS...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST-3EP1N8AW400S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.