INDUSTRIAL COMPONENT DATA

# PC 5/ 2-GU-7,62 GY7035 1713275 PHOENIX CONTACT Printed-circuit board connector

**Brand: PHOENIX CONTACT | Manufacturer Part Number: PC 5/ 2-GU-7,62 GY7035**

PRODUCT IMAGE\nNOT AVAILABLE

| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | PC 5/ 2-GU-7,62 GY7035 |
| Catalog number | 1713275 |
| Category | Printed circuit board connector |
| Minimum order | 50 Pcs |
| Document ID | EO-5B02782BD6 |
| Generated | 2026-11-19 |

## Product Overview

Printed-circuit board connector
Printed circuit board base housing, nominal section: 6 mm², color: luminous gray, nominal current: 41 A, nominal voltage (III/2): 630 V, contact surface: Tin, contact type: Male, number of rows: 1, number of poles: 2, family of articles: PC 5/.. -GU, pitch: 7.62 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 4.2 mm, number of solder pins per potential: 3, plug-in system: COMBICON PC 5, Plug-in face orientation: inverted, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |

## Additional Product Information

Key Commercial Data
Orderkey 1713275
Packing unit 1
GTIN 4055626355924
Custom tariff number 85366930
Dimensions
Length [ l ] 29.25 mm
Width 18.04 mm
Pitch 7.62 mm
Dimension a 7.62 mm

Width [ w ] 18.04 mm
Height [ h ] 17.74 mm
Height 13.54 mm
Length of the solder pin 4.2 mm
Pin spacing 7.62 mm
Length 29.25 mm
General
Range of articles PC 5/..-GU
Insulating material group I
Rated voltage (III/2) 630 V
Nominal current IN 41 A
Insulating material PA
Flammability rating according to UL 94 V0
Color light gray
Number of positions 2
Standards and Regulations
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 5.0EC002637ETIM 6.0EC002637

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PC 5/ 2-GU-7,62 GY7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.