INDUSTRIAL COMPONENT DATA

ST-8EP1N8A6100S 1613595 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST-8EP1N8A6100S



Manufacturer	PHOENIX CONTACT
MPN / Reference	ST-8EP1N8A6100S
Catalog number	1613595
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-1DB4C0B13E
Generated	2026-11-18

Product Overview

Device connector, front mounting
Conect. plug. to be apar. front wall, straight, for standard and SPEEDCON locking, M17, number of poles: 5+3+PE, contact type: Male, Axial O-ring, Central fixing, shielded: yes, protection index: IP67, number of poles: 9, connection type: Crimped connection, series: ST, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1242794

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1613595
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 145 (C-2-2017)
GTIN 4046356442053
Weight per Piece (excluding packing) 21.000 g
Custom tariff number 85366990
Country of origin DE (Germany)
General
Note Order information: Order crimp contacts 5 x 0.6 mm, 4 x Ø 1 mm separately
Type of locking for standard and SPEEDCON interlock

Direction of rotation of contact chamber numbering Standard
Coding N
Contact connection method Crimp connection
Type of contacts Pin
Number of positions 9
Contact diameter of power contacts 1 mm
Nominal current per power contact at 25°C 14 A
Contact diameter of signal contacts 0.6 mm
Nominal current per signal contact at 25°C 3.6 A
Pg housing screw connection none
Mounting type Central fixing
Ambient conditions
Ambient temperature -40 °C ... 125 °C
Degree of protection IP67
Specifications according to DIN EN 61984:2001
Installation height max. 3000 m
Nominal / operating voltage of power contacts 630 V
Rated surge voltage of power contacts 6 kV
Overvoltage category of power contacts III
Degree of pollution of power contacts 3
Nominal / operating voltage of signal contacts 60 V
Rated surge voltage of signal contacts 1.5 kV
Overvoltage category of signal contacts III
Degree of pollution of signal contacts 3
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufactu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST-8EP1N8A6100S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.