INDUSTRIAL COMPONENT DATA

ST-8EP1N8AAC00S 1613608 PHOENIX CONTACT Device connector, front mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST-8EP1N8AAC00S



Manufacturer	PHOENIX CONTACT
MPN / Reference	ST-8EP1N8AAC00S
Catalog number	1613608
Category	Sensor-actuator connector chassis
Minimum order	16 Pcs
Document ID	EO-44E93B501D
Generated	2026-11-18

Product Overview

Device connector, front mounting
Conect. plug. to be apar. front wall, Swivel angle, SPEEDCON lock, M17, number of poles: 5+3+PE, contact type: Pin, Axial
O-ring, 4x Ø2.7, shielded: yes, flange size: 25 mm x 25 mm, number of poles: 9, connection type: Crimped connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1613608
Packing unit 16 pc
Note Made to Order (non-returnable)
GTIN 4046356442152
Weight per Piece (excluding packing) 97.960 g
Custom tariff number 85366990
Country of origin DE (Germany)
General
Note Order information: Order crimp contacts 5 x 0.6 mm, 4 x Ø 1 mm separately
Type of locking SPEEDCON locking
Direction of rotation of contact chamber numbering Standard
Coding N

Contact connection method Crimp connection
Type of contacts Pin
Number of positions 9
Contact diameter of power contacts 1 mm
Nominal current per power contact at 25°C 14 A
Contact diameter of signal contacts 0.6 mm
Nominal current per signal contact at 25°C 3.6 A
Pg housing screw connection none
Mounting type 4x Ø2,7
Ambient conditions
Ambient temperature -40 °C ... 125 °C
Degree of protection IP67
Material
Housing material Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Specifications according to DIN EN 61984:2001
Installation height max. 3000 m
Nominal / operating voltage of power contacts 630 V
Rated surge voltage of power contacts 6 kV
Overvoltage category of power contacts III
Degree of pollution of power contacts 3
Nominal / operating voltage of signal contacts 60 V
Rated surge voltage of signal contacts 1.5 kV
Overvoltage category of signal contacts III
Degree of pollution of signal contacts 3
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST-8EP1N8AAC00S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.