
INDUSTRIAL COMPONENT DATA

ST 2,5-PCBV/ 4-G-5,2 1980501 PHOENIX CONTACT Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST 2,5-PCBV/ 4-G-5,2



Manufacturer	PHOENIX CONTACT
MPN / Reference	ST 2,5-PCBV/ 4-G-5,2
Catalog number	1980501
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-ABD4BA597F
Generated	2026-11-18

Product Overview

Feed-through header
ST-COMBI coupling, connection direction perpendicular to the printed circuit board, pitch: 5.2 mm, number of poles: 4

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Key Commercial Data
Orderkey 1980501
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
Catalog page Page 293 (C-1-2017)
GTIN 4017918972172
Weight per Piece (excluding packing) 6.580 g
Custom tariff number 85366930
Country of origin PL (Poland)
Dimensions
Length [l] 18.05 mm
Width 22.9 mm
Pitch 5.2 mm

Width [w] 22.9 mm
Height [h] 21.7 mm
Length 18.05 mm
General
Range of articles ST 2,5-PCBV/..-G
Insulating material group I
Maximum load current 24 A (with 4 mm² conductor cross section)
Insulating material PA
Flammability rating according to UL 94 V0
Color gray
Internal cylindrical gage A3
Number of positions 4
Standards and Regulations
Connection in acc. with standard CUL
Flammability rating according to UL 94 V0
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637
UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC 13.239121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST 2,5-PCBV/ 4-G-5,2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.