INDUSTRIAL COMPONENT DATA

ST-REL2-KG120/1 2823654 PHOENIX CONTACT Relay connectors

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST-REL2-KG120/1



Manufacturer	PHOENIX CONTACT
MPN / Reference	ST-REL2-KG120/1
Catalog number	2823654
Category	Switching relay
Minimum order	1 Pcs
Document ID	EO-04C7158A9D
Generated	2026-11-18

Product Overview

Relay connectors
Plug-in relay bracket, equipped with mini-switching relay, contacts (AgNi): Medium to large powers, 1 open contact, input voltage 120 V AC/DC, with light indication, pluggable into base terminal blocks

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays

Additional Product Information

Key Commercial Data
Orderkey 2823654
Packing unit 10 pc
Catalog page Page 87 (IF-2005)
GTIN 4017918077495
Weight per Piece (excluding packing) 33.480 g
Custom tariff number 85364900
Country of origin DE (Germany)
Dimensions
Width 14.6 mm
Height 33 mm
Depth 66.5 mm
Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
Coil side
Nominal input voltage UN 120 V AC/DC
Input voltage range in reference to UN 0.8 ... 1.06
Typical input current at UN 5 mA
Typical response time 7 ms (with DC)
Typical release time 11 ms (with DC)
Protective circuit Bridge rectifier, varistor
Operating voltage display yes
Power dissipation for nominal condition 0.6 W
Contact side
Contact type Single contact, 1 N/O contact
Type of switch contact Single contact
Contact material AgNi
Maximum switching voltage 250 V AC/DC
Maximum inrush current 8 A
Limiting continuous current 6 A
Interrupting rating (ohmic load) max. 95 W (at 24 V DC)
50 W (at 48 V DC)
45 W (at 60 V DC)
45 W (at 110 V DC)
75 W (at 220 V DC)
1500 VA (for 250 V AC)
General
Test voltage relay winding/relay contact 2.5 kV AC (50 Hz, 1 min.)
Operating mode 100% operating factor
Mechanical service life approx. 2x 107cycles
Net weight (SAP) 33.48 g
Standards and Regulations
Standards/regulations DIN VDE 0110b, Gr. C for 250 V DC
IEC 60255/DIN VDE 0435 (in relevant parts)
DIN EN 50178/DIN VDE 0160 (in relevant parts)
EN 60730/DIN VDE 0631
DIN VDE 0160 (in relevant parts)
Environ...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST-REL2-KG120/1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.