INDUSTRIAL COMPONENT DATA

ST-REL3-SG-B 24/21/P 2824255 PHOENIX CONTACT Relay connectors

Brand: PHOENIX CONTACT | Manufacturer Part Number: ST-REL3-SG-B 24/21/P



Manufacturer	PHOENIX CONTACT
MPN / Reference	ST-REL3-SG-B 24/21/P
Catalog number	2824255
Category	Switching relay
Minimum order	1 Pcs
Document ID	EO-9107EC3B81
Generated	2026-11-19

Product Overview

Relay connectors
Relay connector, equipped with mini-residual switching relay, contacts (AgSnO): small to large powers, 1 inverter contact, 24 V DC input voltage, with free-flowing diode and polarity reversal protection diode, switching to positive

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays

Additional Product Information

Key Commercial Data
Orderkey 2824255
Packing unit 10 pc
Catalog page Page 88 (IF-2005)
GTIN 4017918077631
Weight per Piece (excluding packing) 34.130 g
Custom tariff number 85364190
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Width 20.8 mm
Height 33 mm

Depth 66.5 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 50 °C
Ambient temperature (storage/transport) -40 °C ... 70 °C
Coil side
Nominal input voltage UN 24 V DC
Input voltage range in reference to UN 0.8 ... 1.1
Typical input current at UN typ. 8 mA
Typical response time 5 ms
Typical release time 5 ms
Coil voltage 24 V DC
Protective circuit Free-wheeling diode Damping diode
Reverse polarity protection Polarity protection diode
Pulse time range 30 ms ... 5 s
Power dissipation for nominal condition 0.19 W
Contact side
Contact type Single contact, 1-PDT
Type of switch contact Single contact
Contact material AgSnO
Maximum switching voltage 250 V AC/DC
Minimum switching voltage 5 V (At 5 V)
24 V (at 24 V)
Min. switching current 1 mA (at 24 V)
100 mA (At 5 V)
Maximum inrush current 8 A
Limiting continuous current 6 A
Interrupting rating (ohmic load) max. 144 W (at 24 V DC)
43 W (at 48 V DC)
42 W (at 60 V DC)
55 W (at 110 V DC)
100 W (at 220 V DC)
1500 VA (for 250 V AC)
General
Test voltage relay winding/relay contact 2 kVrms(50 Hz, 1 min.)
Operating mode 100% operating factor
Mechanical service life approx. 107cy...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ST-REL3-SG-B 24/21/P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.