INDUSTRIAL COMPONENT DATA

STTB 2,5 OG 3035373 PHOENIX CONTACT Double-level spring-cage terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: STTB 2,5 OG



Manufacturer	PHOENIX CONTACT
MPN / Reference	STTB 2,5 OG
Catalog number	3035373
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-8A952163F3
Generated	2026-11-18

Product Overview

Double-level spring-cage terminal block
Double-deck spring terminal block, nominal voltage: 500 V, nominal current: 22 A, connection type: Spring connection, Sizing cross-section: 2.5 mm², cross-section: 0.08 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, color: orange
Double-level spring-cage terminal block, nom. voltage: 500 V, nominal current: 22 A, connection method: Spring-cage connection, Rated cross section: 2.5 mm2, cross section: 0.08 mm2 - 4 mm2, mounting type: NS 35/7,5, NS 35/15, color: orange

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3035373
Packing unit 50 pc
Minimum order quantity 50 pc
GTIN 4046356122795
Weight per Piece (excluding packing) 9.640 g
Custom tariff number 85369010
Country of origin DE (Germany)
General
Number of levels 2

Number of connections 4
Nominal cross section 2.5 mm²
Color orange
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.77 W (the value is multiplied when connecting multiple levels)
Connection in acc. with standard IEC 60947-7-1
Nominal current IN 22 A
Maximum load current 26 A (with 4 mm² conductor cross section)
Nominal voltage UN 500 V
Open side panel Yes
Dimensions
Width 5.2 mm
Length 67.5 mm
Height NS 35/7,5 47.5 mm
Height NS 35/15 55 mm
Connection data
Connection method Spring-cage connection
Conductor cross section solid min. 0.08 mm²
Conductor cross section solid max. 4 mm²
Conductor cross section flexible min. 0.08 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section AWG min. 28
Conductor cross section AWG max. 12
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²
2 conductors with...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / STTB 2,5 OG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.