

INDUSTRIAL COMPONENT DATA

SUBCON 15HD/M 2708546 PHOENIX CONTACT D-SUB connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SUBCON 15HD/M



Manufacturer	PHOENIX CONTACT
MPN / Reference	SUBCON 15HD/M
Catalog number	2708546
Category	D-Sub connector
Minimum order	1 Pcs
Document ID	EO-3F96C25674
Generated	2026-09-23

Product Overview

D-SUB connector

D-SUB connector, 15 HD (High Density) poles, plug, one cable entry under 35°, universal model for all systems, pin arrangement: 1, 2, 3, 6, 7, 8, 10, 13, 14 in screw connection terminal.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Safety
--------------	--------------------------

Additional Product Information

Key Commercial Data

Orderkey 2708546

Packing unit 1 pc

GTIN 4017918942144

Weight per Piece (excluding packing) 44.000 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Width 16 mm

Height 55 mm

Length 56.5 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 75 °C

Ambient temperature (storage/transport) -25 °C ... 80 °C

Altitude 5000 m (For restrictions see manufacturer's declaration)

Degree of protection IP40

General

Nominal voltage UN 24 V AC/DC

Signal VGA

Insertion/withdrawal cycles ≥ 200

Housing material ABS, metal-plated

Connection data

Connection D-SUB connection

Number of positions 15

Connection method High density D-SUB pin strip

Tightening torque 0.4 Nm

Connection PCB connection

Number of positions 9

Connection method Screw connection

Conductor cross section flexible min. 0.14 mm²

Conductor cross section flexible max. 1 mm²

Conductor cross section solid min. 0.14 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section AWG min. 26

Conductor cross section AWG max. 16

Stripping length 5 mm

Tightening torque 0.25 Nm

Standards and Regulations

Free from substances that could impair the application of coating according to P-VW 3.10.7 57 65 0 VW-AUDI-Seat central standard

Noxious gas test ISA-S71.04-1985 G3 Harsh Group A

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declarati..."

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SUBCON 15HD/M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.