INDUSTRIAL COMPONENT DATA

AB-PTI 4/3 3214053 PHOENIX CONTACT Support bracket

Brand: PHOENIX CONTACT | Manufacturer Part Number: AB-PTI 4/3



Manufacturer	PHOENIX CONTACT
MPN / Reference	AB-PTI 4/3
Catalog number	3214053
Category	Busbar support
Minimum order	50 Pcs
Document ID	EO-E3E2550FF4
Generated	2026-11-18

Product Overview

Support bracket
Easel, Busbar holder, place every 20 cm, length: 116 mm, width: 2.2 mm, height: 46 mm, number of poles: 1, color: blue
Support bracket, Bracket for busbars, set every 20 cm, depth: 46 mm, width: 2.2 mm, height: 116 mm, number of positions: 1, color: blue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataProduct propertiesProduct type Support bracket
Number of positions 1
Data management status
Article revision 01
DimensionsWidth 2.2 mm
Height 116 mm
Depth 46 mm
Depth on NS 35/7,5 47.1 mm
Depth on NS 35/15 54.6 mm
Material specificationsColor blue (RAL 5015)
Material PA
Flammability rating according to UL 94 V0
Static insulating material application in cold -60 °C

Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly) -5 °C ... 70 °C
Ambient temperature (actuation) -5 °C ... 70 °C
Permissible humidity (operation) 20 % ... 90 %
Permissible humidity (storage/transport) 30 % ... 70 %

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AB-PTI 4/3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.