INDUSTRIAL COMPONENT DATA

VAL-MS 230/2+0-FM 2800102 PHOENIX CONTACT Type 2 surge arrester

Brand: PHOENIX CONTACT | Manufacturer Part Number: VAL-MS 230/2+0-FM



Manufacturer	PHOENIX CONTACT
MPN / Reference	VAL-MS 230/2+0-FM
Catalog number	2800102
Category	Surge protection device for power supply systems
Minimum order	1 Pcs
Document ID	EO-B77D903ED3
Generated	2026-11-18

Product Overview

Type 2 surge arrester
2-pole surge arrester for rail mounting for 2+0 circuit, with thermal-dynamic control, optical fault indication and remote indication contact,

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

Key Commercial Data
Orderkey 2800102
Packing unit 1 pc
Catalog page Page 41 (C-6-2015)
GTIN 4046356499675
Weight per Piece (excluding packing) 257.500 g
Custom tariff number 85363030
Country of origin DE (Germany)
Dimensions
Height 96.8 mm
Width 35.6 mm
Depth 65.7 mm (incl. DIN rail 7.5 mm)
Horizontal pitch 2 Div.

Ambient conditions
Degree of protection IP20 (only when all terminal points are used)
Ambient temperature (operation) -40 °C ... 80 °C
Ambient temperature (storage/transport) -40 °C ... 80 °C
Altitude <= 2000 m (amsl (above mean sea level))
Permissible humidity (operation) 5 % ... 95 %
Shock (operation) 25g (Half-sine / 11 ms / 3x ±X, ±Y, ±Z)
Vibration (operation) 5g (10 ... 500 Hz / 2.5 h / X, Y, Z)
General
IEC test classification II
T2
EN type T2
IEC power supply system TN-C
Mode of protection L-PEN
Mounting type DIN rail: 35 mm
Color jet black RAL 9005
Housing material PA 6.6
PBT
Degree of pollution 2
Flammability rating according to UL 94 V-0
Type DIN rail module, two-section, divisible
Surge protection fault message Optical, remote indicator contact
Protective circuit
Nominal voltage UN 240/415 V AC (TN-C)
Nominal frequency fN 50 Hz (60 Hz)
Maximum continuous voltage UC 275 V AC
Rated load current IL 80 A
Residual current IPE <= 0.9 mA
Standby power consumption PC <= 240 mVA
Nominal discharge current In(8/20) µs 20 kA
Maximum discharge current Imax(8/20) µs 40 kA
Short-circuit current rating ISCCR 25 kA
Voltage protection level Up <= 1.35 kV
Residual voltage Ures....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VAL-MS 230/2+0-FM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.