INDUSTRIAL COMPONENT DATA

# VAL-MS 385/80/3+1-FM 2920968 PHOENIX CONTACT Type 2 surge arrester

**Brand: PHOENIX CONTACT | Manufacturer Part Number: VAL-MS 385/80/3+1-FM**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | VAL-MS 385/80/3+1-FM |
| Catalog number | 2920968 |
| Category | Surge protection device for power supply systems |
| Minimum order | 1 Pcs |
| Document ID | EO-9E79D1E4EC |
| Generated | 2026-11-18 |

## Product Overview

Type 2 surge arrester

Type 2 surge arrester for 5-conductor power systems (L1, L2, L3, N, PE), with connector lock and remote indication contact.

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Trabtech (TT) |

## Additional Product Information

Key Commercial Data
Orderkey 2920968
Packing unit 1 pc
Catalog page Page 49 (C-6-2015)
GTIN 4046356280983
Weight per Piece (excluding packing) 599.350 g
Custom tariff number 85363030
Country of origin DE (Germany)
Dimensions
Height 98.7 mm
Width 71.2 mm
Depth 77.5 mm (incl. DIN rail 7.5 mm)
Horizontal pitch 4 Div.
Ambient conditions

Degree of protection IP20 (only when all terminal points are used)
Ambient temperature (operation) -40 °C ... 80 °C
Ambient temperature (storage/transport) -40 °C ... 80 °C
Altitude <= 2000 m (amsl (above mean sea level))
Permissible humidity (operation) 5 % ... 95 %
Shock (operation) 30g (Half-sine / 11 ms / 3x ±X, ±Y, ±Z)
Vibration (operation) 7.5g (10 ... 500 Hz / 2.5 h / X, Y, Z)
General
IEC test classification II
T2
EN type T2
IEC power supply system TT
TN-C
TN-S
Mode of protection L-N
L-PE
N-PE
Mounting type DIN rail: 35 mm
Color jet black RAL 9005
Housing material PA 6.6
PBT
Degree of pollution 2
Flammability rating according to UL 94 V-0
Type DIN rail module, two-section, divisible
Surge protection fault message Optical, remote indicator contact
Protective circuit
Nominal voltage UN 240/415 V AC (TN-S)
240/415 V AC (TT)
Nominal frequency fN 50 Hz (60 Hz)
Maximum continuous operating voltage UC(L-N) 385 V AC
Maximum continuous operating voltage UC(L-PE) 358 V AC
Maximum continuous voltage UC(N-PE) 264 V AC
Rated load current IL 80 A
Residual current IPE <= 5 µA
Standby power consumption PC <= 690 mVA
Nominal discharge current In(8/20) µs 40 k...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VAL-MS 385/80/3+1-FM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.