INDUSTRIAL COMPONENT DATA

VAL-MS 350 VF ST 2856595 PHOENIX CONTACT Type 2 surge protection plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: VAL-MS 350 VF ST



Manufacturer	PHOENIX CONTACT
MPN / Reference	VAL-MS 350 VF ST
Catalog number	2856595
Category	Accessories/spare parts for surge protection power supply systems
Minimum order	1 Pcs
Document ID	EO-5A757D05B0
Generated	2026-11-18

Product Overview

Type 2 surge protection plug
Type 2 plug-in surge protection with series circuit consisting of varistor and gas-filled arc arrester for VAL-MS base element, with thermal control, optical fault indication. Execution: 350 V AC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

Key Commercial Data
Orderkey 2856595
Packing unit 10 pc
Catalog page Page 63 (C-4-2017)
GTIN 4017918876869
Weight per Piece (excluding packing) 37.800 g
Custom tariff number 85363010
Country of origin DE (Germany)
Dimensions
Height 52.4 mm
Width 17.5 mm
Depth 55.3 mm
Horizontal pitch 1 Div.

Ambient conditions
Degree of protection IP20
Ambient temperature (operation) -40 °C ... 80 °C
Ambient temperature (storage/transport) -40 °C ... 80 °C
Altitude <= 2000 m (amsl (above mean sea level))
Permissible humidity (operation) 5 % ... 95 %
Shock (operation) 25g (Half-sine / 11 ms / 3x ±X, ±Y, ±Z)
Vibration (operation) 5g (10 ... 500 Hz / 2.5 h / X, Y, Z)
General
IEC test classification II
T2
EN type T2
IEC power supply system TN
TT
IT
Mode of protection L-N
L-PE
L-PEN
Mounting type on base element
Color jet black RAL 9005
Housing material PA 6.6
Degree of pollution 2
Flammability rating according to UL 94 V-0
Type DIN rail module, two-section, divisible
Number of positions 1
Arrester can be tested with CHECKMASTER from software version: From SW rev. 1.12
Surge protection fault message optical
Additional descriptions
Note Usable in all low-voltage systems between L-N or L-PEN.
Only usable in IT Systems between L-PE, if the exposed-conductive-parts (bodies) of the equipment of the low-voltage installation is connected to the earthing arrangement of the transformer substation. (interconnected earthing arrangement of the HV-transformer substation with the bodies of the LV-installation. R...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VAL-MS 350 VF ST with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.