INDUSTRIAL COMPONENT DATA

PT 2X2-HF-12 DC-ST 2839570 PHOENIX CONTACT Surge protection plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 2X2-HF-12 DC-ST



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 2X2-HF-12 DC-ST
Catalog number	2839570
Category	Surge protection device for data networks/MCR-technology
Minimum order	1 Pcs
Document ID	EO-59F3A385BA
Generated	2026-11-18

Product Overview

Surge protection plug
Plug-in surge protection for base element, coarse and fine transverse voltage protection for two two-wire circuits without earth potential in information technology. Workmanship: 12 V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

Key Commercial Data
Orderkey 2839570
Packing unit 10 pc
Catalog page Page 161 (C-4-2017)
GTIN 4017918591113
Weight per Piece (excluding packing) 22.150 g
Custom tariff number 85363010
Country of origin DE (Germany)
Dimensions
Height 45 mm
Width 17.7 mm
Depth 52 mm
Horizontal pitch 1 Div.

Ambient conditions
Ambient temperature (operation) -40 °C ... 85 °C
Degree of protection IP20
General
Housing material PA
Flammability rating according to UL 94 V-0
Color black
Standards for cearances and creepage distances DIN VDE 0110-1
IEC 60664-1
Mounting type on base element
Type Male
Number of positions 5
Direction of action Line-Line & Line-Signal Ground/Shield & optional Signal Ground/Shield-Earth Ground
Arrester can be tested with CHECKMASTER from software version: From SW rev. 1.00
Protective circuit
IEC test classification C1
C2
C3
D1
VDE requirement class C1
C2
C3
D1
Nominal voltage UN 12 V DC
Maximum continuous voltage UC 13 V DC
9 V AC
Rated current 450 mA (45°C)
Operating effective current ICat UC <= 5 µA
Residual current IPE <= 4 µA (with PT 2X2-BE)
<= 1 µA (with PT 2X2+F-BE)
Nominal discharge current In(8/20) µs (line-line) 10 kA
Nominal discharge current In(8/20) µs (line-earth) 10 kA
Pulse discharge current Iimp(10/350) µs 2.5 kA
Total discharge current Itotal(8/20) µs 20 kA
Max. discharge current Imax(8/20) µs maximum (line-line) 10 kA
Max. discharge current Imax(8/20) µs maximum (line-earth) 10 kA
Nominal pulse current Ian (10/1000) µs (line-line) 67 A
Output voltage limita...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 2X2-HF-12 DC-ST with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.