INDUSTRIAL COMPONENT DATA

SAC-3P-M12T/2XM12 B PE 1519723 PHOENIX CONTACT T distributor

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M12T/2XM12 B PE



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-M12T/2XM12 B PE
Catalog number	1519723
Category	Sensor actuator adapter
Minimum order	1 Pcs
Document ID	EO-3790F6F72A
Generated	2026-11-18

Product Overview

T distributor
T Distributor, 5-Pole, Unshielded, M12 Straight Connector, Coding: A, A Straight Female M12, Coding: A, Jumped 2+4 PIN and Straight Female M12, Coding: A, Bridged 2+4 PIN

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1519723
Packing unit 1 pc
Catalog page Page 258 (C-2-2017)
GTIN 4046356019910
Weight per Piece (excluding packing) 25.600 g
Custom tariff number 85366990
Country of origin DE (Germany)
Ambient conditions
Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)
Degree of protection IP65
IP67
General

Rated current at 40°C 4 A
Rated voltage 48 V AC
60 V DC
Number of positions 5
Insulation resistance >= 100 M?
Coding A - standard
Standards/regulations M12 connector IEC 61076-2-101
Status display No
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Torque 0.4 Nm (M12 connector)
Material
Flammability rating according to UL 94 HB
Contact material CuZn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-101
Flammability rating according to UL 94 HB
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
Classifications
eCl@ss 4.027060306eCl@ss 4.127060306eCl@ss 5.027061801eCl@ss 5.127061800eCl@ss 6.027279200eCl@ss 7.027440104eCl@ss 8.027440102eCl@ss 9.027440106
ETIM 2.0EC000830ETIM 3.0EC001855ETIM 4.0EC001855ETIM 5.0EC002062ETIM 6.0EC002925
UNSPSC 6.0131251501UNSPSC 7.090131251501UNSPSC 1131251501UNSPSC 12.0131251501UNSPSC 13.231251501

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M12T/2XM12 B PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.