INDUSTRIAL COMPONENT DATA

TC-XC96-DI32-EX-PR-HIMAX02 2908751 PHOENIX CONTACT Termination Carrier for redundantly connecting 32 MACX An..

Brand: PHOENIX CONTACT | Manufacturer Part Number: TC-XC96-DI32-EX-PR-HIMAX02

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	TC-XC96-DI32-EX-PR-HIMAX02
Catalog number	2908751
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-772FD969A8
Generated	2026-11-18

Product Overview

Termination Carrier for redundantly connecting 32 MACX Analog Ex i signal conditioners to digital input cards of the HIMA HIMax controller, via one C96 connector, 96-pos. Suitable for the HIMax X-DI 32 02 card
Termination Carrier for the redundant connection of 32 MACX Analog Ex-i separation amplifiers to HIMA-HIMax control system's digital input cards, via a C96, 96-pole connector. Suitable for HIMax X-DI 32 02 card

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Technical dataNotesNotes on operation For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
Utilization restriction
EMC note EMC: class A product, see manufacturer's declaration in the download area
Product propertiesProduct type Module carrier
Data management status
Article revision 05
Insulation characteristics: Air clearances and creepage distances
Insulation Basic insulation
Overvoltage category II
Pollution degree 2

Electrical propertiesMax. permissible current 1 A (Signal/channel)
Nominal voltage UN < 50 V DC (Per signal/channel)
Air clearances and creepage distances
Rated insulation voltage 30 V
Rated surge voltage 0.5 kV
Supported controller HIMA HIMax
Suitable I/O card X-DI 32 02
Supply
Designation Device supply
Fuse 2x 2.5 A Slow-blow (exchangeable)
Input voltage 24 V DC
Input voltage range 19.2 V DC ... 30 V DC
Input current <= 2 A
Redundant supply yes, decoupled from diodes
Polarization and surge protection Yes
Output name Switching output
Contact switching type 1 N/C contact (alarm = open)
Maximum switching voltage 30 V DC (2 A)
Connection dataPower supply
Connection method Screw connection
Stripping length 7 mm
Number of connections 1
Number of positions 6
Conductor cross section rigid 0.75 mm² ... 2.5 mm²
Conductor cross section flexible 0.75 mm² ....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TC-XC96-DI32-EX-PR-HIMAX02 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.