INDUSTRIAL COMPONENT DATA

HC-B 24-A-UT-PER-M 1648108 PHOENIX CONTACT Terminal adapter

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-B 24-A-UT-PER-M



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-B 24-A-UT-PER-M
Catalog number	1648108
Category	Contact insert for rectangular connectors
Minimum order	5 Pcs
Document ID	EO-82CB5CDBA9
Generated	2026-11-18

Product Overview

Terminal adapter
HEAVYCON terminal adapter with plug insert, B24 series, 24 poles, ground connection on the left for the right side of the control cabinet, screw connection.
HEAVYCON terminal adapter male insert, B24 series, 24-pos., left protective conductor connection for the right side of the control cabinet, screw connection.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Technical dataNotesGeneral For HEAVYCON-ADVANCE mounting flange and HEAVYCON panel mounting base of B24 type
General Connectors may be operated only when there is no load/voltage.
Product propertiesProduct type Terminal adapter
Product family HC-B
Series HC-B
Type B24
Number of positions 24
Connection profile 24+PE
Contact numbering 1 - 24
Type for the right side of the control cabinet

Screwdriver blade 0.5 x 3.5 mm
Data management status
Article revision 08
Insulation characteristics
Overvoltage category III
Degree of pollution 3
Electrical propertiesRated voltage (III/3) 500 V
Rated surge voltage 6 kV
Rated current 16 A
SCCR 5 kA (UL 2237)
Connection dataConnection technology
Connection technology Screw connection
Connection in acc. with standard IEC / EN
Conductor connection
Conductor cross section 0.5 mm² ... 2.5 mm²
Connection cross section AWG 20 ... 14
Tightening torque 0.5 Nm ... 0.8 Nm
Stripping length of the individual wire 12 mm
DimensionsDimensional drawing
Width 34 mm
Height 71.6 mm
Length 111 mm
Drill hole distance, horizontal 104 mm
Drill hole distance, vertical 27 mm
Material specificationsFlammability rating according to UL 94 V0
Contact material Copper alloy
Contact surface material Ag
Contact carrier material PA
Standards/regulations PA: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3)
Cable/lineStripping length of the individual wire 12 mm
Mechanical propertiesMechanical data
Insertion/wit...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-B 24-A-UT-PER-M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.