INDUSTRIAL COMPONENT DATA

HC-B 6-A-DT-PEL-M 1648364 PHOENIX CONTACT Terminal adapter

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-B 6-A-DT-PEL-M



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-B 6-A-DT-PEL-M
Catalog number	1648364
Category	Contact insert for rectangular connectors
Minimum order	5 Pcs
Document ID	EO-65095E8B82
Generated	2026-11-18

Product Overview

Terminal adapter
HEAVYCON terminal block adapter with plug insert, B6 series, 6 poles, for the left side of the control cabinet, push-in connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data
Orderkey 1648364
Packing unit 5 pc
Catalog page Page 543 (C-2-2017)
GTIN 4046356092081
Weight per Piece (excluding packing) 72.380 g
Custom tariff number 85366990
Country of origin CN (China)
Dimensions
Drill hole distance, horizontal 44 mm
Height 70.5 mm
Ambient conditions
Degree of protection (IP) IP20

Ambient temperature (operation) -40 °C ... 125 °C
Electrical characteristics
Number of positions 6
Rated voltage (III/3) 500 V
Rated surge voltage 6 kV
Rated current 16 A
Mechanical characteristics
Type B6
Connection method Push-in connection
Stripping length of the individual wire 10 mm (13 mm if ferrules are used)
Conductor cross section 0.5 mm² ... 2.5 mm²
Connection cross section AWG 22 ... 12
General
Note For HEAVYCON-ADVANCE mounting flange and HEAVYCON panel mounting base of B6 type
Connectors may be operated only when there is no load/voltage.
Contact material Copper alloy
Contact surface material Ag
Contact carrier material PA
Standards/regulations PA: Fire protection in rail vehicles - requirement sets R22 and R23 acc. to DIN EN 45545-2 (Risk level HL1 - HL2)
PA: Fire protection in rail vehicles - requirement set R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3)
Degree of pollution 3
Overvoltage category III
Flammability rating according to UL 94 V0
Assembly instructions To ensure correct use, installation in housing with IP54 protection or better is required
Installation instructions 1) Use ferrules. 0.5 mm² ... 2.5 mm² with insulating collar,....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-B 6-A-DT-PEL-M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.