INDUSTRIAL COMPONENT DATA

HC-D 40-A-TWIN-PEL-M 1580150 PHOENIX CONTACT Terminal adapter

Brand: PHOENIX CONTACT | Manufacturer Part Number: HC-D 40-A-TWIN-PEL-M



Manufacturer	PHOENIX CONTACT
MPN / Reference	HC-D 40-A-TWIN-PEL-M
Catalog number	1580150
Category	Contact insert for rectangular connectors
Minimum order	1 Pcs
Document ID	EO-DBEBE1E6FF
Generated	2026-11-18

Product Overview

Terminal adapter
HEAVYCON terminal block adapter with plug insert, D40 series, 40 poles, PE connection on the right for the left side of the control cabinet, push-in connection
HEAVYCON terminal adapter male insert, D40 series, 40-pos., right PE connection for the left side of the control cabinet, push-in connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Technical dataNotesGeneral For HEAVYCON-ADVANCE mounting flange and HEAVYCON panel mounting base of B16 type
General Connectors may be operated only when there is no load/voltage.
Product propertiesProduct type Terminal adapter
Product family HC-D
Series HC-D
Type B16
Number of positions 40
Connection profile 40+PE
Type for the left side of the control cabinet
Data management status

Article revision 09
Insulation characteristics
Overvoltage category III
Degree of pollution 3
Electrical propertiesRated voltage (III/3) 250 V
Rated surge voltage 4 kV
Rated current 10 A
SCCR 5 kA (UL 2237)
Connection dataConnection technology
Connection technology Push-in connection
Conductor connection
Conductor cross section 0.5 mm² ... 2.5 mm²
Connection cross section AWG 22 ... 12
Stripping length of the individual wire 10 mm
DimensionsDimensional drawing
Width 34 mm
Height 139.3 mm
Length 83 mm
Drill hole distance, horizontal 77.5 mm
Drill hole distance, vertical 27 mm
Material specificationsFlammability rating according to UL 94 V0
Contact material Copper alloy
Contact surface material Ag
Contact carrier material PA
Standards/regulations PA: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3)
Cable/lineStripping length of the individual wire 10 mm
Mechanical propertiesMechanical data
Insertion/withdrawal cycles >= 500
Environmental and real-life conditionsAmbient conditions
Degree of protection IP20
Ambient temperature (operati...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HC-D 40-A-TWIN-PEL-M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.