INDUSTRIAL COMPONENT DATA

# UC-TMF 8 BU CUS 0824655 PHOENIX CONTACT Marker for terminal blocks

**Brand: PHOENIX CONTACT | Manufacturer Part Number: UC-TMF 8 BU CUS**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | UC-TMF 8 BU CUS |
| Catalog number | 0824655 |
| Category | Labelling for terminal block |
| Minimum order | 1 Pcs |
| Document ID | EO-2DC019CAE8 |
| Generated | 2026-11-18 |

## Product Overview

Marker for terminal blocks
Terminal marker, available: by mats, blue, labeled according to customer's instructions, mounting class: fit in flat index groove, for terminal width: 8.2 mm, usable surface: 7.6 x 5.1 mm, Number of individual indices: 56

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > CABINET add-on |

## Additional Product Information

Key Commercial Data
Orderkey 0824655
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 63 (C-5-2013)
GTIN 4046356359900
Weight per Piece (excluding packing) 8.700 g
Custom tariff number 49119900
Country of origin DE (Germany)
Dimensions
Width (a) 8 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 120 °C

Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
General
Color blue
Type flat
Components free from silicone and halogen
Flammability rating according to UL 94 V2
Material PA
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 56
Number of individual labels per row 7
Printability UV LED technology
Device 5147999 BLUEMARK CLED
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Marking mounting type snap into flat marker groove
Result Test passed
Oxygen index (DIN EN ISO 4589-2) 28,2%
Class I 3
Class F 2
R22 HL 1 - HL 2
R23 HL 1 - HL 2
R24 HL 1 - HL 2
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
F...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UC-TMF 8 BU CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.



Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.