
INDUSTRIAL COMPONENT DATA

# UC1-TMF 4 GN CUS 0828337 PHOENIX CONTACT Marker for terminal blocks

**Brand: PHOENIX CONTACT | Manufacturer Part Number: UC1-TMF 4 GN CUS**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | UC1-TMF 4 GN CUS |
| Catalog number | 0828337 |
| Category | Labelling for terminal block |
| Minimum order | 1 Pcs |
| Document ID | EO-66DD713D39 |
| Generated | 2026-11-18 |

## Product Overview

Marker for terminal blocks
Terminal marker, available: by mats, green, labeled according to customer's instructions, mounting class: fit into flat index groove, for terminal width: 4.2 mm, usable area: 3.45 x 5.2 mm, Number of individual indices: 120

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > CABINET add-on |

## Additional Product Information

Key Commercial Data
Orderkey 0828337
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 120 (C-5-2013)
GTIN 4046356485203
Weight per Piece (excluding packing) 6.190 g
Custom tariff number 49119900
Country of origin DE (Germany)
Dimensions
Width (a) 4 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 120 °C

General
Color green
Type flat
Components free from silicone and halogen
Flammability rating according to UL 94 V2
Material PA
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 120
Number of individual labels per row 15
Printability UV LED technology
Plotter
Device 5147999 BLUEMARK CLED
5144615 CMS-P1-PLOTTER
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Marking mounting type snap into flat marker groove
Result Test passed
Oxygen index (DIN EN ISO 4589-2) 28,2%
Class I 3
Class F 2
R22 HL 1 - HL 2
R23 HL 1 - HL 2
R24 HL 1 - HL 2
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Flammability rating according to UL 94 V2
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UC1-TMF 4 GN CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.