INDUSTRIAL COMPONENT DATA

UCT-TMF 12 VT CUS 0829690 PHOENIX CONTACT Marker for terminal blocks

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCT-TMF 12 VT CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCT-TMF 12 VT CUS
Catalog number	0829690
Category	Labelling for terminal block
Minimum order	1 Pcs
Document ID	EO-ABD174CE0A
Generated	2026-11-18

Product Overview

Marker for terminal blocks
Marker for terminals, available: by mats, violet, labeled according to customer's instructions, mounting class: fit in groove for flat index, for terminal width: 12 mm, usable surface: 11.2 x 4.7 mm, Number of individual indices: 30
Marker for terminal blocks, can be ordered: by sheet, violet, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 12 mm, Number of individual labels: 30

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Technical dataProduct propertiesProduct type Labeled terminal marker
Pitch 12 mm
Type flat
Data management status
Article revision 01
Marking
Number of individual labels 30
Number of individual labels per row 5
Identification technology Thermal transfer for sheets and cards
MountingMounting type snap into flat marker groove
Material specificationsRoHS compliant yes

Color violet (RAL 4005)
Material PC
Flammability rating according to UL 94 V0
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Components free from silicone and halogen
Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish
Result Test passed
UV resistance
Specification ISO 4892-2:2013-03 (following)
Result Test passed
Test duration 96 h
Ambient conditions
Ambient temperature (operation) -40 °C ... 120 °C
Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
DimensionsWidth 11.45 mm
Height 1.64 mm
Length 5 mm
Pitch 12 mm
Standards and regulationsWipe resistance DIN EN 61010-1 (VDE 0411-1)
NotesGeneral Can be labeled via thermal transfer

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCT-TMF 12 VT CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.