INDUSTRIAL COMPONENT DATA

# DFK 4-SI(6,3X32) BK 0708344 PHOENIX CONTACT Fuse panel feed-through terminal block

**Brand: PHOENIX CONTACT | Manufacturer Part Number: DFK 4-SI(6,3X32) BK**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | DFK 4-SI(6,3X32) BK |
| Catalog number | 0708344 |
| Category | Panel feed-through terminal block |
| Minimum order | 50 Pcs |
| Document ID | EO-E5EBE2D404 |
| Generated | 2026-11-18 |

## Product Overview

Fuse panel feed-through terminal block
Borne grommets, number of poles: 1, width: 12.2 mm, color: black

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |

## Additional Product Information

Key Commercial Data
Orderkey 0708344
Packing unit 50 pc
Note Made to Order (non-returnable)
Catalog page Page 639 (C-1-2013)
GTIN 4017918004613
Weight per Piece (excluding packing) 16.480 g
Custom tariff number 85369010
Country of origin BG (Bulgaria)
General
Number of levels 1
Number of connections 2
Color black
Insulating material PA

Flammability rating according to UL 94 V2
Maximum load current 10 A
6.3 A
Rated surge voltage 4 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Connection in acc. with standard IEC 60947-7-3
Nominal current IN 10 A
Maximum load current 10 A
Nominal voltage UN 400 V
Open side panel No
Number of positions 1
Dimensions
Width 12.2 mm
Length 51 mm
Pitch 6 mm
Plate thickness 1.5 mm
Connection data
Connection side Level 1 ext. 1
Connection method Screw connection
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 6 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 4 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 10
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 4 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²
2 conductors with same cross section, solid min. 0.2 mm²
2 conductors with same cross section, sol...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFK 4-SI(6,3X32) BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.