INDUSTRIAL COMPONENT DATA

IB IL AO 1/U/SF-PAC 2861399 PHOENIX CONTACT Inline terminal

Brand: PHOENIX CONTACT | Manufacturer Part Number: IB IL AO 1/U/SF-PAC



Manufacturer	PHOENIX CONTACT
MPN / Reference	IB IL AO 1/U/SF-PAC
Catalog number	2861399
Category	Fieldbus, decentr. periphery - analogue I/O module
Minimum order	1 Pcs
Document ID	EO-84406CEC55
Generated	2026-11-18

Product Overview

Inline terminal
Inline, Analog output terminal, Analog output: 1, 0 V ... 10 V, connection technology: 2 conductors, transmission rate on the local bus: 500 kBit/s, protection rating: IP20, including inline connector and marking surface
Inline, Analog output terminal, Analog output: 1, 0 V ... 10 V, connection technology: 2-conductor, transmission speed in the local bus: 500 kbps, degree of protection: IP20, including Inline connector and labeling field

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > I/O

Additional Product Information

Technical dataDimensionsDimensional drawing
Width 12.2 mm
Height 135 mm
Depth 71.5 mm
NotesNote on application
Note on application Only for industrial use
Utilization restriction
CCCex note Use in potentially explosive areas is not permitted in China.
InterfacesInline local bus
Number of interfaces 2
Connection method Inline data jumper

Transmission speed 500 kbps
Transmission physics Copper
System propertiesModule
ID code (dec.) 125
ID code (hex) 7D
Length code (hex) 01
Length code (dec) 01
Process data channel 16 bit
Input address area 0 Byte
Output address area 2 Byte
Register length 16 bit
Required parameter data 4 Byte
Required configuration data 4 Byte
Output dataAnalog:
Output name Analog output
Connection technology 2-conductor
Note regarding the connection technology shielded
Number of outputs 1
D/A converter resolution 16 bit
Protective circuit Transient protection of outputs
Representation of output values 16 bits (15 bits + sign)
DAC resolution 16 bit
Process data update < 1 ms
Voltage output signal 0 V ... 10 V
Load/output load voltage output > 2 k? 0.05 %
Product propertiesProduct type I/O component
Product family Inline
Type modular
Scope of delivery including Inline connector and labeling field
Data management status
Article revision 10
Insulation characteristics
Overvoltage category II (IEC 60664-1, EN 60664-1)
Pollution degree 2 (IEC 60664-1, EN 60664-1)
Electrical propertiesMaximum power dissipation for nominal condition 0.8 W
Potentials: Communications po...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IB IL AO 1/U/SF-PAC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.