
INDUSTRIAL COMPONENT DATA

# PTB 2,5-PE/L/MT 3210549 PHOENIX CONTACT Installation ground terminal block

**Brand: PHOENIX CONTACT | Manufacturer Part Number: PTB 2,5-PE/L/MT**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | PTB 2,5-PE/L/MT |
| Catalog number | 3210549 |
| Category | Multi level installation terminal block |
| Minimum order | 50 Pcs |
| Document ID | EO-01D905369A |
| Generated | 2026-11-18 |

## Product Overview

Installation ground terminal block
Ground terminal for distribution, nominal voltage: 400 V, nominal current: 22 A, Push-in connection, Dimensioning cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², Push-in connection, Dimensioning cross-section: 2.5 mm², cross-section: 0.14 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, colour: grey

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Modular TBs |

## Additional Product Information

Key Commercial Data
Orderkey 3210549
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
Catalog page Page 89 (C-1-2017)
GTIN 4046356701341
Weight per Piece (excluding packing) 21.960 g
Custom tariff number 85369010
Country of origin PL (Poland)
General
Number of levels 3

Number of connections 5
Nominal cross section 2.5 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 4 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.77 W (the value is multiplied when connecting multiple levels)
Nominal current IN 22 A (with a 2.5 mm² conductor cross section)
Maximum load current 30 A (with 4 mm² conductor cross section and 3-pos. terminal block)
Nominal voltage UN 400 V (phase conductor/phase conductor)
250 V (phase conductor/PE)
Nominal current IN(upper level) 16 A (with a 2.5 mm² conductor cross section)
Maximum load current (upper level) 16 A (with 4 mm² conductor cross section)
Nominal voltage UN 250 V
Open side panel Yes
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 7.3 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 1.89 kV
Checking the mechanical stability of terminal points (5 x conductor connection) Tes...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTB 2,5-PE/L/MT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.