
INDUSTRIAL COMPONENT DATA

QTC 2,5-TWIN BU 3206461 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: QTC 2,5-TWIN BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	QTC 2,5-TWIN BU
Catalog number	3206461
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-1715C844A8
Generated	2026-11-18

Product Overview

Feed-through terminal block
Feed-through terminal, nominal voltage: 800 V, nominal current: 24 A, number of connections: 3, connection type: Quick connection, 1st floor, Dimensioning cross-section: 2.5 mm², cross-section: 0.5 mm² - 2.5 mm², mounting class: NS 35/7.5, NS 35/7.5, colour: blue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Key Commercial Data
Orderkey 3206461
Packing unit 50 pc
Minimum order quantity 50 pc
Catalog page Page 209 (C-1-2017)
GTIN 4046356057646
Weight per Piece (excluding packing) 12.000 g
Custom tariff number 85369010
Country of origin CN (China)
General
Number of levels 1
Number of connections 3

Potentials 1
Nominal cross section 2.5 mm²
Color blue
Insulating material PA
Flammability rating according to UL 94 V0
Area of application Railway industry
Machine building
Plant engineering
Process industry
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.77 W
Ambient temperature (actuation) -10 °C ... 90 °C
Maximum load current 24 A (at a conductor cross section of 2.5 mm²; it must not be exceeded by the total current.)
Nominal current IN 24 A (with a 2.5 mm² conductor cross section)
Nominal voltage UN 800 V
Open side panel Yes
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 9.8 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 2 kV
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed
Result of bending test Test passed
Bending test rotation speed 10 rpm
Bending test turns 135
Bending test conductor cross section/weight 0.5 m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / QTC 2,5-TWIN BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.