
INDUSTRIAL COMPONENT DATA

QTTCB 1,5/ 2P-PV 3206377 PHOENIX CONTACT Double-level terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: QTTCB 1,5/ 2P-PV



Manufacturer	PHOENIX CONTACT
MPN / Reference	QTTCB 1,5/ 2P-PV
Catalog number	3206377
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-9A046F736B
Generated	2026-11-18

Product Overview

Double-level terminal block
Double-level terminal block, Current and voltage are determined by the connector used., with potential splicers, rated voltage: 500 V, rated current: 17.5 A, connection type: Quick connect / plug-in connection, Sizing cross-section: 1.5 mm², cross-section: 0.25 mm² - 1.5 mm², mounting class: NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Enclosures connectivity

Additional Product Information

Key Commercial Data
Orderkey 3206377
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
Catalog page Page 335 (C-1-2017)
GTIN 4017918976002
Weight per Piece (excluding packing) 13.300 g
Custom tariff number 85369010
Country of origin PL (Poland)
General
Number of levels 2

Number of connections 4
Potentials 1
Nominal cross section 1.5 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Area of application Railway industry
Machine building
Plant engineering
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.56 W (the value is multiplied when connecting multiple levels)
Ambient temperature (operation) -50 °C (see derating curve)
Ambient temperature (assembly) -40 °C ... 100 °C
Maximum load current 17.5 A (with 1.5 mm² conductor cross section)
Nominal current IN 17.5 A
Nominal voltage UN 500 V
Open side panel Yes
Insertion/withdrawal cycles mechanical 100
Result of surge voltage test Test passed
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 1.89 kV
Result of tight fit on support Test passed
Setpoint 1 N
Short circuit stability result Test passed
Conductor cross section short circuit testing 1.5 mm²
Short-time current 0.18 kA
Result of thermal test Test passed
Proof of thermal characteristics (needle flame) effective duration 30 s
Oscillation, broadband noise test r...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / QTTCB 1,5/ 2P-PV with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.