
INDUSTRIAL COMPONENT DATA

STTBU 4-PE 3033171 PHOENIX CONTACT Double-level spring-cage terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: STTBU 4-PE



Manufacturer	PHOENIX CONTACT
MPN / Reference	STTBU 4-PE
Catalog number	3033171
Category	Ground terminal block
Minimum order	50 Pcs
Document ID	EO-6852595DE8
Generated	2026-11-18

Product Overview

Double-level spring-cage terminal block
Double-level spring terminal block, number of connections: 4, connection type: Spring connection, cross-section: 0.08 mm² - 6 mm², connection type: Screw connection, cross-section: 0.14 mm² - 6 mm², mounting type: NS 35/7.5, NS 35/15, colour: yellow-green
Double-deck spring terminal block, connection type: Spring connection, cross-section: 0.08 mm2 - 6 mm2, connection type: Screw connection, cross-section: 0.14 mm2 - 6 mm2, mounting: NS 35/7.5, NS 35/15, colour: yellow-green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3033171
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
Catalog page Page 179 (C-1-2017)
GTIN 4046356148061
Weight per Piece (excluding packing) 23.260 g
Custom tariff number 85369010
Country of origin PL (Poland)

General
Number of levels 2
Number of connections 4
Nominal cross section 4 mm²
Color green-yellow
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Connection method Spring-cage connection
Connection in acc. with standard IEC 60947-7-2
Maximum load current 36 A (with 6 mm² conductor connection)
Connection method Screw connection
Connection in acc. with standard IEC 60947-7-2
Maximum load current 36 A (with 6 mm² conductor connection)
Nominal current IN with 4 mm² conductor cross section
Open side panel Yes
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Oscillation, broadband noise test result Test passed
Test specification, oscillation, broadband noise DIN EN 50155 (VDE 0115-200):2008-03
Test spectrum Service life test category 1, class B, body mounted
Test frequency f1= 5 Hz to f2= 150 Hz
ASD level 1.857 (m/s2)2/Hz
Acceleration 0,8 g
Test duration per axis 5 h
Test directions X-, Y- and Z-axis
Shock test result Test passed
Test specification, shock test DIN EN 50155 (VDE 0115-200):2008-03
Shock f...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / STTBU 4-PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.