

INDUSTRIAL COMPONENT DATA

UK 10,3-CC HESI N 3048580 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 10,3-CC HESI N



Manufacturer	PHOENIX CONTACT
MPN / Reference	UK 10,3-CC HESI N
Catalog number	3048580
Category	Fuse terminal block
Minimum order	12 Pcs
Document ID	EO-F6B6831FAD
Generated	2026-09-20

Product Overview

Fuse modular terminal block

Fuse terminal block, fuse type: Glass/ceramic/..., fuse type: DC class, rated voltage: 600 V, rated current: 30 A, connection type: Screw connection, Sizing cross-section: 25 mm², cross-section: 1.5 mm²- 25 mm², mounting class: NS 35/7.5, NS 35/15, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3048580

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 463 (C-1-2017)

GTIN 4046356115971

Weight per Piece (excluding packing) 51.840 g

Custom tariff number 85369095

Country of origin DE (Germany)

Note

Trade restriction The products are offered exclusively for export outside the EU and the European Economic Area.

General

Number of levels 1
Number of connections 2
Nominal cross section 25 mm²
Color black
Insulating material PA
Flammability rating according to UL 94 V0
Maximum power dissipation for nominal condition 3.26 W
Fuse Class CC
Fuse type Glass / ceramics / ...
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group IIIb
Maximum load current 30 A (the current and voltage are determined by the fuse)
Nominal current I_N 32 A (the current and voltage are determined by the fuse)
Nominal voltage U_N 600 V (the current and voltage are determined by the fuse)
Open side panel No
Dimensions
Width 18 mm
Length 81 mm
Height NS 35/7,5 65.5 mm
Height NS 35/15 73 mm
Connection data
Conductor cross section solid min. 1.5 mm²
Conductor cross section solid max. 25 mm²
Conductor cross section flexible min. 1.5 mm²
Conductor cross section flexible max. 25 mm²
Conductor cross section AWG min. 16
Conductor cross section AWG max. 4
Conductor cross section flexible, with ferrule without plastic sleeve min. 1.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 16 mm²
Conductor c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 10,3-CC HESI N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.