

INDUSTRIAL COMPONENT DATA

UK 10,3-HESILED N 690 3048399 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UK 10,3-HESILED N 690



Manufacturer	PHOENIX CONTACT
MPN / Reference	UK 10,3-HESILED N 690
Catalog number	3048399
Category	Fuse terminal block
Minimum order	12 Pcs
Document ID	EO-706CFD4FCC
Generated	2026-09-20

Product Overview

Fuse modular terminal block

Fuse terminal block, fuse type: Glass/ceramic/..., fuse type: 10.3 x 38 mm, nominal voltage: 690 V, nominal current: 32 A, connection type: Screw connection, Sizing cross-section: 16 mm², cross-section: 1.5 mm²- 25 mm², mounting class: NS 35/7.5, NS 35/15, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3048399

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 462 (C-1-2017)

GTIN 4017918976309

Weight per Piece (excluding packing) 52.000 g

Custom tariff number 85369095

Country of origin DE (Germany)

General

Number of levels 1

Number of connections 2

Nominal cross section 16 mm²
Color black
Insulating material PA
Flammability rating according to UL 94 V0
Maximum power dissipation for nominal condition 2.43 W
Fuse 10:3 x 38 mm
Fuse type Glass / ceramics / ...
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group IIIb
Connection in acc. with standard IEC 60947-1/-3
Maximum load current 32 A (the current and voltage are determined by the fuse)
Nominal current I_N 32 A (the current and voltage are determined by the fuse)
Nominal voltage U_N 690 V (the current and voltage are determined by the fuse)
Open side panel No
Dimensions
Width 18 mm
Length 86.7 mm
Height NS 35/7,5 65.5 mm
Height NS 35/15 73 mm
Connection data
Conductor cross section solid min. 1.5 mm²
Conductor cross section solid max. 25 mm²
Conductor cross section flexible min. 1.5 mm²
Conductor cross section flexible max. 25 mm²
Conductor cross section AWG min. 16
Conductor cross section AWG max. 4
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.75 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 16 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UK 10,3-HESILED N 690 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.