INDUSTRIAL COMPONENT DATA

UKK 5-HESILED 24 (5X20) 3026654 PHOENIX CONTACT Fuse modular terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UKK 5-HESILED 24 (5X20)



Manufacturer	PHOENIX CONTACT
MPN / Reference	UKK 5-HESILED 24 (5X20)
Catalog number	3026654
Category	Fuse terminal block
Minimum order	50 Pcs
Document ID	EO-94FED154BE
Generated	2026-11-18

Product Overview

Fuse modular terminal block
Fuse terminal block, fuse type: Glass/ceramic/..., fuse type: G/5 x 20, nominal voltage: 24 V, nominal current: 32 A, connection type: Screw connection, cross-section: 0.2 mm²- 4 mm², Sizing cross-section: 1.5 mm², mounting class: NS 35/7.5, NS 35/15, NS 32, colour: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3026654
Packing unit 50 pc
Catalog page Page 456 (C-1-2017)
GTIN 4017918164188
Weight per Piece (excluding packing) 35.110 g
Custom tariff number 85369095
Country of origin PL (Poland)
General
Note For terminal marking, please use marking material with 8.2 mm pitch.
For lever marking, please use flat marking material with 8.2 mm pitch.
Number of levels 2

Number of connections 4
Nominal cross section 4 mm²
Color black
Insulating material PA
Flammability rating according to UL 94 V0
Maximum power dissipation for nominal condition 4 W (the value is multiplied when connecting multiple levels)
Fuse G / 5 x 20
Fuse type Glass / ceramics / ...
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation max. 1.6 W (With single arrangement of the fuse terminal block in the event of overload)
max. 1.6 W (With interconnected arrangement of several fuse terminal blocks in the event of overload)
max. 4 W (With single arrangement of the fuse terminal block in the event of a short-circuit)
max. 2.5 W (With interconnected arrangement of several fuse terminal blocks in the event of a short-circuit)
LED voltage range 15 V AC/DC ... 30 V AC/DC
LED current range 1 mA ... 2.4 mA
Connection in acc. with standard IEC 60947-7-3
Maximum load current 32 A
Nominal current IN 32 A
Nominal voltage UN 24 V
Maximum load current (upper level) 10 A
Nominal current IN(upper level) 10 A
Nominal voltage UN 400 V
Open...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UKK 5-HESILED 24 (5X20) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.