
INDUSTRIAL COMPONENT DATA

UT 4-PE/L-DIO/R-L P/P 3046235 PHOENIX CONTACT Component terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UT 4-PE/L-DIO/R-L P/P



Manufacturer	PHOENIX CONTACT
MPN / Reference	UT 4-PE/L-DIO/R-L P/P
Catalog number	3046235
Category	Ground terminal block
Minimum order	50 Pcs
Document ID	EO-1157625B14
Generated	2026-11-18

Product Overview

Component terminal block
Terminal block for components, with threaded sockets for test sockets to accommodate test pins, nominal voltage: 500 V, nominal current: 0.5 A, number of connections: 2, connection type: Screw connection, Dimensioning section: 4 mm², cross-section: 0.14 mm² - 6 mm², mounting class: NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3046235
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
Catalog page Page 239 (C-1-2017)
GTIN 4046356416269
Weight per Piece (excluding packing) 21.300 g
Custom tariff number 85369010
Country of origin PL (Poland)
General
Number of levels 1

Number of connections 2
Nominal cross section 4 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Overvoltage category III
Maximum power dissipation for nominal condition 1.02 W
Maximum load current 0.5 A
Nominal current IN 0.5 A
Nominal voltage UN 500 V
Open side panel Yes
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Fire protection for rail vehicles...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UT 4-PE/L-DIO/R-L P/P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.