
INDUSTRIAL COMPONENT DATA

UT 4-QUATTRO HV RD 3048849 PHOENIX CONTACT Four-conductor universal terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UT 4-QUATTRO HV RD



Manufacturer	PHOENIX CONTACT
MPN / Reference	UT 4-QUATTRO HV RD
Catalog number	3048849
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-AC3B2EC165
Generated	2026-11-18

Product Overview

Four-conductor universal terminal block
Four-conductor universal terminal block, nominal voltage: 1000 V, nominal current: 32 A, number of connections: 4, connection type: Screw connection, 1st floor, Sizing cross-section: 4 mm², cross-section: 0.14 mm² - 6 mm², mounting class: NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3048849
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
Catalog page Page 55 (NTK-2012)
GTIN 4046356517584
Weight per Piece (excluding packing) 16.710 g
Custom tariff number 85369010
Country of origin CN (China)
General
Number of levels 1

Number of connections 4
Potentials 1
Nominal cross section 4 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 1.02 W
Maximum load current 37 A (In the case of a 6 mm² conductor cross section, the maximum load current must not be exceeded by the total current of all connected conductors)
Nominal current IN 32 A
Nominal voltage UN 1000 V
Open side panel Yes
Dimensions
Width 6.2 mm
End cover width 2.2 mm
Length 65.4 mm
Height NS 35/7,5 50 mm
Height NS 35/15 57.5 mm
Connection data
Connection method Screw connection
Screw thread M3
Stripping length 9 mm
Tightening torque, min 0.6 Nm
Tightening torque max 0.8 Nm
Connection in acc. with standard IEC 60947-7-1
Conductor cross section solid min. 0.14 mm²
Conductor cross section solid max. 6 mm²
Conductor cross section AWG min. 26
Conductor cross section AWG max. 10
Conductor cross section flexible min. 0.14 mm²
Conductor cross section flexible max. 6 mm²
Min. AWG conductor cross section, flexible 26
Max. AWG conductor cross section, flexible 10
Conductor cros...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UT 4-QUATTRO HV RD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.