INDUSTRIAL COMPONENT DATA

UTI 16-PE 3073830 PHOENIX CONTACT Installation ground terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UTI 16-PE



Manufacturer	PHOENIX CONTACT
MPN / Reference	UTI 16-PE
Catalog number	3073830
Category	Ground terminal block
Minimum order	1 Pcs
Document ID	EO-6CDC59C744
Generated	2026-11-18

Product Overview

Installation ground terminal block
Ground terminal for distribution, number of connections: 2, number of poles: 1, connection type: Screw connection, 1st floor, right-hand connection, Dimensioning cross-section: 16 mm², cross-section: 6 mm² - 25 mm², fastening type: PE foot with fixing screw, M4, mounting class: NS 35/7.5, NS 35/15, colour: yellow-green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3073830
Packing unit 50 pc
Catalog page Page 253 (C-1-2017)
GTIN 4046356347259
Weight per Piece (excluding packing) 47.820 g
Custom tariff number 85369010
Country of origin CN (China)
General
Number of positions 1
Number of levels 1
Number of connections 2

Nominal cross section 16 mm²
Color green-yellow
Insulating material PA
Flammability rating according to UL 94 V2
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Open side panel No
Terminal block mounting 1.5 Nm ... 1.8 Nm (PE foot with mounting screw, M4)
Oscillation, broadband noise test result Test passed
Test specification, oscillation, broadband noise DIN EN 50155 (VDE 0115-200):2008-03
Test spectrum Service life test category 1, class B, body mounted
Test frequency f1= 5 Hz to f2= 150 Hz
ASD level 0.02 g²/Hz
Acceleration 0,8 g
Test duration per axis 5 h
Test directions X-, Y- and Z-axis
Shock test result Test passed
Test specification, shock test DIN EN 50155 (VDE 0115-200):2008-03
Shock form Half-sine
Acceleration 5 g
Shock duration 30 ms
Number of shocks per direction 3
Test directions X-, Y- and Z-axis (pos. and neg.)
Relative insulation material temperature index (Elec., UL 746 B) 125 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 115 °C
Dimensions
Width 12.2 mm
Length 51 mm
Height 49.9 mm
Height NS 35/7,5 50.5 mm
Height NS 35/15 58 mm
Connection data
Note Please observe the current carrying capacity of the...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UTI 16-PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.