INDUSTRIAL COMPONENT DATA

# UTI 35-PE 3074091 PHOENIX CONTACT Installation ground terminal block

**Brand: PHOENIX CONTACT | Manufacturer Part Number: UTI 35-PE**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | UTI 35-PE |
| Catalog number | 3074091 |
| Category | Multi level installation terminal block |
| Minimum order | 1 Pcs |
| Document ID | EO-5959BD5379 |
| Generated | 2026-11-18 |

## Product Overview

Installation ground terminal block
Ground terminal block for distribution, Screw connection, Sizing cross-section: 35 mm², cross-section: 0.75 mm² - 35 mm², installation class: NS 35/7.5, NS 35/15, color: yellow-green

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Modular TBs |

## Additional Product Information

Key Commercial Data
Orderkey 3074091
Packing unit 50 pc
Catalog page Page 255 (C-1-2017)
GTIN 4046356347273
Weight per Piece (excluding packing) 67.110 g
Custom tariff number 85369010
Country of origin CN (China)
General
Number of levels 1
Number of connections 2
Potentials 2
Nominal cross section 35 mm²

Color green-yellow
Insulating material PA
Flammability rating according to UL 94 V2
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Nominal current IN 125 A
Nominal voltage UN 800 V
Open side panel No
Terminal block mounting 2.5 Nm ... 3 Nm (PE foot with mounting screw, M5)
Dimensions
Width 15 mm
Length 55 mm
Height NS 35/7,5 51 mm
Height NS 35/15 58.5 mm
Connection data
Note Please observe the current carrying capacity of the DIN rails.
Connection method Screw connection
Screw thread M6
Stripping length 16 mm
Tightening torque, min 3.2 Nm
Tightening torque max 3.7 Nm
Connection in acc. with standard IEC 60947-7-2
Conductor cross section solid min. 0.75 mm²
Conductor cross section solid max. 35 mm²
Conductor cross section AWG min. 18
Conductor cross section AWG max. 2
Conductor cross section flexible min. 0.75 mm²
Conductor cross section flexible max. 35 mm²
Min. AWG conductor cross section, flexible 18
Max. AWG conductor cross section, flexible 2
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.75 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 35 mm²
Conductor cro...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UTI 35-PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.