INDUSTRIAL COMPONENT DATA

UTTB 2,5/2P-PE 3060380 PHOENIX CONTACT Protective conductor double-level terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UTTB 2,5/2P-PE



Manufacturer	PHOENIX CONTACT
MPN / Reference	UTTB 2,5/2P-PE
Catalog number	3060380
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-D0212002C7
Generated	2026-11-18

Product Overview

Protective conductor double-level terminal block
Double-floor terminal block conductor protection, Current and voltage are determined by the connector used., connection type: Screw connection / plug-in connection, cross-section: 0.14 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, color: yellow-green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3060380
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
Catalog page Page 339 (C-1-2017)
GTIN 4046356132190
Weight per Piece (excluding packing) 18.420 g
Custom tariff number 85369010
Country of origin PL (Poland)
General
Number of levels 2

Number of connections 4
Nominal cross section 2.5 mm²
Color green-yellow
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Connection method Screw/plug-in connection
Connection in acc. with standard IEC 61984
Maximum load current 22 A (with 4 mm² conductor cross section)
22 A (with 4 mm² conductor cross section)
Open side panel Yes
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UTTB 2,5/2P-PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.