INDUSTRIAL COMPONENT DATA

UTTB 4-MT P/P LA 24 RD/O-U 3046773 PHOENIX CONTACT Knife disconnect terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UTTB 4-MT P/P LA 24 RD/O-U



Manufacturer	PHOENIX CONTACT
MPN / Reference	UTTB 4-MT P/P LA 24 RD/O-U
Catalog number	3046773
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-B8BDF692F9
Generated	2026-11-19

Product Overview

Knife disconnect terminal block
Blade interruptible terminal block, with threaded sockets for test sockets to accommodate test pins, nominal voltage: 24 V, nominal current: 30 A, connection type: Screw connection, Sizing section: 4 mm², section: 0.14 mm² - 6 mm², connection type: Screw connection, Sizing section: 4 mm², section: 0.14 mm² - 6 mm², Mounting: NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3046773
Packing unit 50 pc
Note Made to Order (non-returnable)
Catalog page Page 237 (C-1-2017)
GTIN 4046356105675
Weight per Piece (excluding packing) 21.890 g
Custom tariff number 85369010
Country of origin PL (Poland)
General
Number of levels 2
Number of connections 4

Potentials 1
Nominal cross section 4 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 1.02 W (the value is multiplied when connecting multiple levels)
Maximum load current 38 A (with 6 mm² conductor cross section)
Nominal current IN 30 A
Nominal voltage UN 24 V
Maximum load current 20 A (with 6 mm² conductor cross section)
Nominal current IN 20 A
Nominal voltage UN 24 V
Open side panel Yes
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 4.8 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 1.5 kV
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed
Result of bending test Test passed
Bending test rotation speed 10 rpm
Bending test turns 135
Bending test conductor cross section/weight 0.14 mm² / 0.2 kg
4 mm² / 0.9 kg
6 mm2/ 1.4 kg
Tensile test....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UTTB 4-MT P/P LA 24 RD/O-U with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.