

INDUSTRIAL COMPONENT DATA

E S6 A 200X200X160 0899017 PHOENIX CONTACT Junction box

Brand: PHOENIX CONTACT | Manufacturer Part Number: E S6 A 200X200X160



Manufacturer	PHOENIX CONTACT
MPN / Reference	E S6 A 200X200X160
Catalog number	0899017
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-59AD1C4B79
Generated	2026-09-24

Product Overview

Junction box

Terminal box, material: Sterling steel 316L / 1.4404, surface resistance: brushed, silver, 200 mm x 200 mm x 160 mm, type of closure: Screw cap, delivery volume - ATD: Mounting plate, Fixing square with mounting screws, M12 grounding bolt placed on the outside, Installation instructions, Mounting plate

Junction box, material: Stainless steel, 316L/1.4404, surface resistance: brushed, silver, 200 mm x 200 mm x 160 mm, type of locking: Screw-on cover, scope of supply - ATD: Mounting panel, Fixing angle with mounting screws, M12 grounding bolts, affixed externally, Installation notes, Mounting panel

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Enclosures connectivity**

Additional Product Information

Technical dataProduct propertiesProduct type Terminal box

Scope of delivery Mounting panel

Fixing angle with mounting screws

M12 grounding bolts, affixed externally

Installation notes

Type 20

Data management status

Article revision 00

Insulation characteristics

Protection class I**Electrical properties**Maximum power dissipation 17 W (T6 up to 40 °C)

10.6 W (T6 up to 55 °C)

6.3 W (T6 up to 65 °C)

23.4 W (T5 up to 40 °C)

17 W (T5 up to 55 °C)

12.8 W (T5 up to 65 °C)

27.6 W (T4 up to 40 °C)

13.3 W (T4 up to 55 °C)

17 W (T4 up to 65 °C)

DimensionsDimensional drawing

Width 200 mm

Height 200 mm

Depth 160 mm

Clearance width, maximum DIN rail length 144 mm

Max. material thickness 1.5 mm

Material specificationsColor silver

Material Stainless steel, 316L/1.4404

Seal material Silicon

Surface characteristics brushed

Note 240 grain

Mechanical propertiesGeneral

Type of locking (GRP) Screw-on cover Allen screws

Environmental and real-life conditionsAmbient conditions

Ambient temperature (operation) -55 °C ... 135 °C

MountingAssembly note External fixing clips

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEWSend PHOENIX CONTACT / E S6 A 200X200X160 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.