INDUSTRIAL COMPONENT DATA

# C S6 A 480X480X160 0899067 PHOENIX CONTACT Junction box

**Brand: PHOENIX CONTACT | Manufacturer Part Number: C S6 A 480X480X160**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | C S6 A 480X480X160 |
| Catalog number | 0899067 |
| Category | Enclosure/switchgear cabinet (empty) |
| Minimum order | 2 Pcs |
| Document ID | EO-85AF0AC962 |
| Generated | 2026-11-19 |

## Product Overview

Junction box
Empty housing, material: Sterling steel 316L / 1.4404, surface resistance: brushed, silver, 480 mm x 480 mm x 160 mm, type of closure: Door with changeable hinge, delivery volume - ATD: Door hinge with rotating closure with a quarter turn, Mounting plate, Double bit key, Mounting bracket with mounting screws, M12 Grounding Bolt Placed Outside, Installation Instructions, Door Hinge with Twist Lock with Quarter Turn

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Enclosures connectivity |

## Additional Product Information

Key Commercial Data
Orderkey 0899067
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 527 (C-3-2017)
GTIN 4046356928281
Weight per Piece (excluding packing) 11,690.000 g
Custom tariff number 94032080
General
Scope of supply Door hinge with quarter turn locking
Mounting plate

Double-bit key
Fixing angle with mounting screws
M12 grounding bolts, affixed externally
Installation notes
Color silver
Dimensions
Width 480 mm
Height 480 mm
Depth 160 mm
Clearance width, maximum DIN rail length 848 mm
Max. material thickness 1.5 mm
General
Housing material Stainless steel, 316L/1.4404
Surface characteristics brushed
Note 240 grain
Cover fastening Door with replaceable hinge
Note Quarter turn locking with two-way key bit
Fixing device External fixing clips
Seal material Silicon
Ambient conditions
Degree of protection of housing (IP) IP66
Protection class I
Degree of protection (IK) 7.00 J
Temperature in operating conditions -55 °C ... 135 °C
Classifications
eCl@ss 10.0.127180190eCl@ss 4.027180101eCl@ss 4.127180101eCl@ss 5.027180502eCl@ss 5.127180100eCl@ss 6.027180100eCl@ss 7.027180190eCl@ss 8.027180190eCl@ss 9.027180190
ETIM 4.0EC000261ETIM 5.0EC000261ETIM 6.0EC000261
UNSPSC 13.231261502

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / C S6 A 480X480X160 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.