
INDUSTRIAL COMPONENT DATA

TFKC 2,5/ 2-ST-5,08 YE 1740640 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: TFKC 2,5/ 2-ST-5,08 YE



Manufacturer	PHOENIX CONTACT
MPN / Reference	TFKC 2,5/ 2-ST-5,08 YE
Catalog number	1740640
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-C938103F1E
Generated	2026-11-18

Product Overview

Printed-circuit board connector
Connector for printed circuit board, nominal section: 2.5 mm², color: yellow, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 4, family of articles: TFKC 2.5/.. -ST, pitch: 5.08 mm, connection type: Push-in spring connection, conductor connection/printed circuit board connection direction: 0 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1740640
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
GTIN 4046356292054
Weight per Piece (excluding packing) 4.670 g
Custom tariff number 85366990
Country of origin BG (Bulgaria)
Dimensions

Length [l] 25.7 mm
Width [w] 10.06 mm
Height [h] 22.1 mm
Pitch 5.08 mm
Dimension a 5.08 mm
General
Range of articles TFKC 2,5/..-ST
Number of positions 2
Connection method Push-in spring connection
Rated voltage (III/3) 320 V
Connection in acc. with standard EN-VDE
Nominal current IN 12 A
Nominal cross section 2.5 mm²
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 2.5 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 12
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. 0.5 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. 1.5 mm²
Minimum AWG according to UL/CUL 26
Maximum AWG according to UL/CUL 12
Standards and Regulations
Connection in acc. with standard....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TFKC 2,5/ 2-ST-5,08 YE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.