INDUSTRIAL COMPONENT DATA

# MINI MCR-SL-PTB-FM 2902958 PHOENIX CONTACT Power terminal block

**Brand: PHOENIX CONTACT | Manufacturer Part Number: MINI MCR-SL-PTB-FM**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | MINI MCR-SL-PTB-FM |
| Catalog number | 2902958 |
| Category | Accessories/spare parts for low-voltage switch technology |
| Minimum order | 1 Pcs |
| Document ID | EO-33AB0F7BD3 |
| Generated | 2026-11-19 |

## Product Overview

Power terminal block
The MINI MCR-SL-PTB-FM(-SP) power terminal block is inserted into the rail connector to supply the supply voltage. The FM power terminal offers the additional monitoring function together with the fault monitoring module. Screw connection.

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > INTERFACE Components (IF) |

## Additional Product Information

Key Commercial Data
Orderkey 2902958
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 524 (C-5-2017)
GTIN 4046356702713
Weight per Piece (excluding packing) 82.100 g
Custom tariff number 85369010
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Width 6.2 mm

Height 93.1 mm
Depth 102.5 mm
Ambient conditions
Ambient temperature (operation) -20 °C ... 65 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Output data
Output voltage range Input voltage - 0.8 V
General
Mounting position any
Assembly instructions The T connector can be used to bridge the supply voltage. It can be snapped onto a 35 mm DIN rail according to EN 60715.
Connection data, input
Connection method Screw connection
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 2.5 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section AWG min. 26
Conductor cross section AWG max. 12
Stripping length 12 mm
Screw thread M3
Standards and Regulations
Electromagnetic compatibility Conformance with EMC directive
Noise emission EN 61000-6-4
Standards/regulations EN 61000-4-2
Designation Electromagnetic RF field
Standards/regulations EN 61000-4-3
Evaluation criterion A
Standards/regulations EN 61000-4-4
EN 61000-4-5
Designation Conducted interferences
Standards/regulations EN 61000-4-6
Evaluation criterion A
Confo...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MINI MCR-SL-PTB-FM with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.



Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.