INDUSTRIAL COMPONENT DATA

DFLK-D15 SUB/M/FKCT 2903054 PHOENIX CONTACT Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFLK-D15 SUB/M/FKCT



Manufacturer	PHOENIX CONTACT
MPN / Reference	DFLK-D15 SUB/M/FKCT
Catalog number	2903054
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-E87ACCB7EA
Generated	2026-11-19

Product Overview

Interface module
The VARIOFACE feed-through module makes a 1:1 connection between plug-in push-in spring terminals and a subminiature D-plug (no. 15). A separate mass shunt is available.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2903054
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 590 (C-7-2015)
GTIN 4046356709637
Weight per Piece (excluding packing) 77.500 g
Custom tariff number 85369010
Country of origin DE (Germany)
Dimensions
Width 36.5 mm
Height 58.4 mm
Depth 46 mm

Ambient conditions
Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
General
Max. perm. operating voltage 25 V AC
60 V DC
Max. perm. current (per branch) 2.5 A
Max. permissible current (all branches) 37.5 A
Number of positions 15
Mounting position any
Assembly instructions In rows with zero spacing
Degree of protection IP20
Connection data for connection 1
Connection name Field level
Connection method Plug-in push-in spring-cage connection
Stripping length 10 mm
Conductor cross section solid 0.2 mm² ... 2.5 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Connection data for connection 2
Connection name Controller level
Connection method D-SUB pin strip
Number of positions 15
Standards and Regulations
Connection in acc. with standard CUL
Standards/regulations DIN EN 50178
IEC 60664
Rated insulation voltage 125 V
Rated surge voltage 1.2 kV (Functional insulation)
Degree of pollution 2
Overvoltage category II
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's de...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFLK-D15 SUB/M/FKCT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.