INDUSTRIAL COMPONENT DATA

THERMOMARK CARD 2.0 1085267 PHOENIX CONTACT The THERMOMARK CARD 2.0 thermal transfer printer quickly prints ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: THERMOMARK CARD 2.0



Manufacturer	PHOENIX CONTACT
MPN / Reference	THERMOMARK CARD 2.0
Catalog number	1085267
Category	Printer/scanner/copier
Minimum order	1 Pcs
Document ID	EO-C4A7DBDF6B
Generated	2026-11-19

Product Overview

The THERMOMARK CARD 2.0 thermal transfer printer quickly prints high-quality marking materials in card and mat format. Create high-quality markers for terminal, conductor, cable, equipment, and facility marking applications.
Thermal transfer printer for card-on-card materials, including Europe/US power cable and USB cable. Printed user manual in German and English. Charger for UCT-TM boards... and charger for US cards... For each packaging unit UCT-TM 6, US-EMLP (85.6x54), ink roll = 50 m
Thermal transfer printer for card materials, including Euro/US power cable and USB cable. Support CD includes user manuals in several languages, links to firmware, drivers, and planning and marking software. User manual printed in German and English. Magazine for UCT-TM... sheets and magazines for US-... cards. One Pcs./Pkt. each UCT-TM 6, US-EMLP (85,6x54), ink ribbon = 50 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS devices / software

Additional Product Information

Key Commercial Data
Orderkey 1085267
Packing unit 1 pc
Catalog page Page 35 (C-3-2019)
GTIN 4055626834931

Weight per Piece (excluding packing) 9,980.000 g
Custom tariff number 84433210
Country of origin DE (Germany)
General
Connection data
Classifications
Dimensions
Environmental Product Compliance
General
Interface 10/100 Mbps Ethernet
USB 2.0
Weight 6 kg
Back to topDimensions
Length 325 mm
Height 194 mm
Width 254 mm
Back to topConnection data
Minimum voltage 100 V AC
Max. voltage 240 V AC
Additional text 50 Hz ... 60 Hz
Back to topEnvironmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 10;
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Back to topClassifications
ECLASS
ECLASS 10.0.1 19140104
ECLASS 11.0 19140104
ECLASS 4.0 24010402
ECLASS 4.1 24010402
ECLASS 5.0 19020207
ECLASS 5.1 19020200
ECLASS 6.0 19140100
ECLASS 7.0 19140104
ECLASS 9.0 19140104
Back to topETIM
ETIM 2.0 EC000761
ETIM 3.0 EC000761
ETIM 4.0 EC001672
ETIM 6.0 EC001672
ETIM 7.0 EC001672
Back to topUNSPSC
UNSPSC 6.01 43172501
UNSPSC 7.0901 43212107
UNSPSC 11 43172501
UNSPSC 12.01 43212107
UNSPSC 13.2 43212108

UNSPSC 18.0 43212108
UNSPSC 19.0 43212108
UNSPSC 20.0 43212108
UNSPSC 21.0 43212108
Back to top

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / THERMOMARK CARD 2.0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.