

INDUSTRIAL COMPONENT DATA

TMC 2 F1 120 4,0A 0914840 PHOENIX CONTACT

Thermomagnetic device circuit breaker

Brand: PHOENIX CONTACT | Manufacturer Part Number: TMC 2 F1 120 4,0A



Manufacturer	PHOENIX CONTACT
MPN / Reference	TMC 2 F1 120 4,0A
Catalog number	0914840
Category	Device circuit breaker
Minimum order	1 Pcs
Document ID	EO-1B2FB7E06A
Generated	2026-09-26

Product Overview

Thermomagnetic device circuit breaker

Thermomagnetic protection switch, 2-pole, fast, 1 open contact and 1 closed contacts, with universal foot for mounting on NS 32 or NS 35

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Over Current Protection

Additional Product Information

Key Commercial Data

Orderkey 0914840

Packing unit 3 pc

Note Made to Order (non-returnable)

Catalog page Page 282 (CL-2002)

GTIN 4017918009526

Weight per Piece (excluding packing) 136.430 g

Custom tariff number 85362010

Country of origin DE (Germany)

General

Number of levels 2

Number of connections 4

Mounting type DIN rail: 35 mm

Color black

Number of positions 2

Overvoltage category_GRP II

Insulating material PA66

Flammability rating according to UL 94 V-2

Electrical data

Fuse type Automatic device

Rated surge voltage 2.5 kV

Rated voltage 65 V DC

Rated current IN 4 A

Insulation resistance Riso > 100 M Ω (500 V DC)

Rated short-circuit switching capacity Icn 400 A

2500 A (32 V DC)

Short-circuit switching capacity Ik 2000 A (UL 1077: 65 V DC)

Dielectric strength 3000 V AC (Actuation area)

3000 V AC (Main to auxiliary circuit)

1500 V AC (Position to position)

Switching cycles, max. 10000 (At 1 x In, inductive)

Degree of pollution 2

Overvoltage category_GRP II

Insulating material group II

Dimensions

Height 82.5 mm

Width 25 mm

Depth 96 mm

Ambient conditions

Degree of protection IP30 (Actuation area)

IP20 (Connection area)

Ambient temperature (operation) -30 °C ... 60 °C

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 6 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 4 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 10

Conductor cross section flexible, with ferrule without....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TMC 2 F1 120 4,0A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.