INDUSTRIAL COMPONENT DATA

# TMCP 1 M1 300 4,0A 0915797 PHOENIX CONTACT Thermomagnetic device circuit breaker

**Brand: PHOENIX CONTACT | Manufacturer Part Number: TMCP 1 M1 300 4,0A**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | TMCP 1 M1 300 4,0A |
| Catalog number | 0915797 |
| Category | Device circuit breaker |
| Minimum order | 6 Pcs |
| Document ID | EO-066D50F528 |
| Generated | 2026-11-19 |

## Product Overview

Thermomagnetic device circuit breaker
Thermomagnetic protection switch, 1-pole, semi-flat, 1 open contact and 1 closed contact

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Over Current Protection |

## Additional Product Information

Key Commercial Data
Orderkey 0915797
Packing unit 6 pc
Catalog page Page 281 (CL-2002)
GTIN 4017918600631
Weight per Piece (excluding packing) 46.160 g
Custom tariff number 85362010
Country of origin DE (Germany)
General
Mounting type on base element
Color black
Number of positions 1
Overvoltage category_GRP II
Insulating material PA66

Flammability rating according to UL 94 V-2
Electrical data
Fuse type Automatic device
Rated surge voltage 2.5 kV
Rated voltage 250 V AC
65 V DC
Rated current IN 4 A
Insulation resistance Riso > 100 M? (500 V DC)
Rated short-circuit switching capacity Icn 400 A
2500 A (32 V DC)
Short-circuit switching capacity Ik 5000 A (UL 1077: 277 V AC)
2000 A (UL 1077: 65 V DC)
Dielectric strength 3000 V AC (Actuation area)
1500 V AC (Main to auxiliary circuit)
1000 V AC (Auxiliary circuit 11 - 12 to 23 - 24)
Switching cycles, max. 10000 (At 1 x In, inductive)
Degree of pollution 2
Overvoltage category_GRP II
Insulating material group II
Dimensions
Height 50 mm
Width 12.5 mm
Depth 78.5 mm
Complete module height 115 mm
Complete module width 38 mm
Complete module depth 121 mm
Ambient conditions
Degree of protection IP30 (Actuation area)
IP00 (Connection area)
Ambient temperature (operation) -30 °C ... 60 °C
Connection data
Connection method pluggable
Standards and Regulations
Standards/specifications EN 60934
UL 1077
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
Classifications
eCl@ss 4.027141116eCl@ss 4.127141116eCl@ss 5.027141116eCl@ss 5.127141...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TMCP 1 M1 300 4,0A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.